

GR Pumps

Direct Drive Pumps

Beckett's submersible pump line offers top of the line epoxy encapsulated (not oil filled) design to meet all your continuous duty requirements. They are low maintenance, environmentally safe, and can be used in a variety of industrial applications. Each pump features a heavy-duty motor for maximum output and reliability. GR models have a rotating discharge and a flow control valve for maximum flexibility.



Model #	H	W	L	Outlet	Inlet	Volts	Amps	Watts	Gallons per hour @ 115V, 60Hz						Max Lift (Ft.)	6 Ft. Cord standard
									1'	2'	4'	6'	8'	10'		
G210A	3 3/4"	3 1/2"	4 1/2"	1/4" MNPT, 1/2" I.D. HOSE	SCREEN	115	0.5	25	210	190	137	71	-	-	7.1	✓
G325A	3 3/4"	4"	5"	1/4" MNPT, 1/2" I.D. HOSE	SCREEN	115	0.8	50	340	325	310	265	205	135	12.2	✓
G535A	4"	4"	5 3/8"	1/2" MNPT, 3/4" I.D. HOSE	SCREEN	115	1.2	75	550	520	450	390	295	210	13	✓
GR210A	3 3/4"	3 1/2"	4 1/4"	1/4" MNPT, 1/2" I.D. HOSE	SCREEN	115	0.5	25	190	172	118	58	-	-	6.8	✓
GR325A	3 3/4"	4"	5"	1/4" MNPT, 1/2" I.D. HOSE	SCREEN	115	0.8	50	287	253	234	183	151	120	11.4	✓
G600A	4"	4"	5 3/8"	1/2" MNPT, 3/4" I.D. HOSE	SCREEN	115	1.2	75	590	530	470	380	295	220	12.2	✓
Model #	H	W	L	Outlet	Inlet	Volts	Amps	Watts	Gallons per hour @ 230V, 60Hz						Max Lift (Ft.)	6.5 Ft. Cord standard
									1'	2'	4'	6'	8'	10'		
G210C	3.8"	4.3"	3.5"	1/4" MNPT, 1/2" I.D. HOSE	SCREEN	230	0.3	39	220	190	150	89	-	-	7.1	✓
G325C	3.9"	5.1"	3.8"	1/4" MNPT, 1/2" I.D. HOSE	SCREEN	230	0.4	55	315	290	280	235	-	-	11.6	✓
G535C	4.5"	5.4"	4.0"	1/2" MNPT, 3/4" I.D. HOSE	SCREEN	230	0.7	84	585	545	500	340	210	-	13.2	✓

Average Performance

DESIGNED FOR SUBMERSIBLE USE ONLY!