

GP G & GR Pumps

Parts Washer Pump

GP210V is ideal for most solvent or aqueous parts washer solutions up to 210GPH @ 1 ft. with a maximum pumping height of 7 ft. This model has a viton shaft seal and a threaded cord exit for mounting in a parts washer.

GP325V is ideal for most solvent or aqueous parts washer solutions up to 340GPH @ 1 ft. with a maximum pumping height of 12 ft. This model has a viton shaft seal and a threaded cord exit for mounting in a parts washer.



Model #	H	W	L	Outlet	Inlet	Volts	Amps	Watts	Gallons per hour @ 60Hz / Rated Voltage						Max Lift (ft.)	6 Ft. Cord (No plug)
									1'	2'	4'	6'	8'	10'		
GP210V	3 3/4"	3 1/2"	4 1/2"	1/4" MNPT	SCREEN	115	0.9	50	210	190	137	71	-	-	7	✓
GP210C	3 3/4"	3 1/2"	4 1/2"	1/4" MNPT	SCREEN	230	0.5	40	190	157	93	-	-	-	5	✓
GP325V	5 1/4"	2 1/2"	5 1/4"	1/4" MNPT	SCREEN	115	0.9	50	340	330	300	260	205	135	12	✓
GP325C	5 1/4"	2 1/2"	5"	1/4" MNPT	SCREEN	230	0.5	45	270	260	225	165	120	-	8.5	✓

Average Performance