NEED HELP SELECTING A BECKETT HVAC PUMP?

Condensate Management Solutions. Driven by Innovation Since 1948.



1	What is the Application or Job Type?	CONDENSATE REMOVAL PUMPS	LOW PROFILE CONDENSATE PUMPS	MINI SPLIT CONDENSTATE PUMPS	PLENUM & HIGH TEMPERATURE PUMPS	IN-PAN CONDENSATE PUMPS
	Common Equipment and Installation Examples	Air conditioners, condensing furnaces, boilers, and dehumidifiers	Air conditioners and con- densing furnaces with limited space for pump installation	Wall mounts and ductless, mini-split air conditioners	Above-ceiling and below-floor Plenum applications: con- densing boiler applications	Air conditioners and refrig- eration equipment where in-pan condensate removal is the only option
	Shut Off (Max Lift) Range	12.5' to 65'	20'	53'	20' to 65'	12'
	Flow @ 1 ft, Range	57-476 GPH	145-153 GPH	2.7 GPH	145-476 GPH	80 GPH
	Input Voltage	120V, 230V or 460V	120V or 230V	120V or 230V	120V, 230V or 460V	120V
	Collection Tank Size	.68 qt. to 1 Gal. (US)	.85 qt. (US)	N/A	.85 qt. to 1 Gal. (US)	Included w/ Certain Models
	Maximum Water Temp	150° to 212° F	150° to 190° F	104° F	150° to 212° F	86° F
	Discharge/Check Valve	3/8" to 1/2"	3/8"	1/4"	3/8" to 1/2"	3/8"

2 Other Considerations

Power Supply	6' Cord w/ Plug for CB12, BK17 & BK22. Hard wired terminals for larger pumps.	6' Cord w/ Plug	5' Cord (no plug)	6' Power Lead on CL20. Hard wired terminals for larger pumps.	6' Cord w/ Plug
Safety Switch	Included w/ Most Models	Included w/ Most Models	Yes	Included w/ Most Models	Included w/ Certain Models
PVC Tubing	Included w/ Certain Models	Included w/ Certain Models	Included w/ Certain Models	Included w/ Certain Models	Included w/ Certain Models
UL/CUL Listed	All Models	All Models	All Models	All Models	All Models
UL2043 - Plenum Rated	No	No	No	Yes	No
Standard Warranty	1-3 Year Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty

3 Beckett Pump Models

Featured Pumps					
Learn more at Beckettus.com,	CB12, BK17, BK22, CB22,			CL20, CB50	
contact your local distributor	CB25, CB50 and	CL20 Pumps	MS60 Pumps	and CP65 Pumps	IPC13 Pumps
or your local sales rep for	CP65 Pumps			and CP65 Pullips	
additional information					

SMALL/MEDIUM CONDENSATE PUMPS

Condensate Management Solutions. Driven by Innovation Since 1948.



1	Type of Condensate Removal Pump?	MS60 MINI SPLIT CONDENSTATE PUMPS	CB12 SMALL CONDENSATE PUMP	CL20 LOW PROFILE CONDENSATE PUMP	BK17 MEDIUM CONDENSATE PUMP	BK22 MEDIUM CONDENSATE PUMP
	Shut Off (Max Lift) Range	53'	12.5'	20'	17'	22'
	Flow @ 1 ft, Range	2.7 GPH	57 GPH	145-153 GPH	112 GPH	125 GPH
	Input Voltage	120V or 230V	120V	120V or 230V	120V or 230V	120V or 230V
	Collection Tank Size	N/A	0.68 qt.	.85 qt. (US)	2.5 qt.	2.5 qt.
	Maximum Water Temp	104° F	150° F	150° to 190° F	150° F	150° F
	Discharge/Check Valve	1/4"	3/8"	3/8"	3/8"	3/8"
	Common Equipment and Installation Examples	Wall mounts and ductless, mini-split air conditioners	Air conditioners, condensing furnaces, boilers, and dehumidifiers			

2 Other Considerations

Power Supply	5' Cord (no plug)	6' Cord w/ Plug			
Safety Switch	Yes	Included w/ Certain Models			
PVC Tubing	Included w/ Certain Models	No	No	Included w/ Certain Models	Included w/ Certain Models
UL/CUL Listed	All Models				
UL2043 - Plenum Rated	No	No	Yes, w/ CL201LULP	No	No
Standard Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty	3-Year Warranty	3-Year Warranty

3 Beckett Pump Models

Featured Pumps Learn more at Beckettus.com, contact your local distributor or your local sales rep for	MS601ULQ MS602ULCQ	CB121UL CB121LSUL	CL202UL, CL201LULP, CL202UL, CL202ULHT	BK171UL, BK171LSUL BK171TUL	BK221UL, BK221LSUL, BK221TUL, BK222TUL, BK222UL
additional information					BILLEGE

LARGE & PLENUM CONDENSATE PUMPS

Condensate Management Solutions. Driven by Innovation Since 1948.



Type of Condensate Removal Pump?	CB25 LARGE CONDENSATE PUMP	CB50 LARGE CONDENSATE PUMP	CP65 LARGE CONDENSATE PUMP	PLENUM & HIGH TEMPERATURE CONDENSATE PUMPS	IN-PAN CONDENSATE PUMPS
Shut Off (Max Lift) Range	25'	50'	65'	20' to 65'	12'
Flow @ 1 ft, Range	108 GPH	420-486 GPH	476 GPH	145-476 GPH	80 GPH
Input Voltage	120V or 230V	120V, 230V, 460V	120V, 230V or 460V	120V, 230V or 460V	120V
Collection Tank Size	1 Gal.	1 Gal.	1 Gal.	.85 qt. to 1 Gal. (US)	Included w/ Certain Models
Maximum Water Temp	150°-190° F	150° - 212° F	150° - 212° F	150° to 212° F	86° F
Discharge/Check Valve	3/8"	1/2"	1/2"	3/8"	3/8"
Common Equipment and Installation Examples	Air conditioners, condensing furnaces, boilers, and dehumidifiers	Air conditioners, condensing furnaces, boilers, and dehumidifiers	Air conditioners, condensing furnaces, boilers, and dehumidifiers	Above-ceiling and below-floor Plenum applications: con- densing boiler applications	Air conditioners and refrig- eration equipment where in-pan condensate removal is the only option

2 Other Considerations

Power Supply	Hard Wired Terminal Block	Hard Wired Terminal Block	Hard Wired Terminal Block	6' Power Lead on CL20. Hard Wired Terminals for Larger Pumps.	6' Cord w/ Plug
Safety Switch	Yes, All Models	Yes, All Models	Yes, All Models	Included w/ Most Models	Included w/ Certain Models
PVC Tubing	No	No	No	Included w/ Certain Models	Included w/ Certain Models
UL/CUL Listed	All Models	All Models	All Models	All Models	All Models
UL2043 - Plenum Rated	No	Included w/ Certain Models	Included w/ Certain Models	Yes	No
Standard Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty

3 Beckett Pump Models

Featured Pumps						
Learn more at BeckettUS.com,	CB251UL, CB251ULHT,	CB501UL, CB501ULHTS,	CP651ULHTS	CL20 Pumps		
contact your local distributor	CB2570L, CB2510LITT,	CB502UL, CB502ULHTS,	CP654ULHTS	CB50 Pumps	IPC13 Pumps	
or your local sales rep for	CB2320L, CB2320LIII	CB504UL, CB504ULHTS	CF0540LITI5	CP65 Pumps		
additional information				-		



NEW BK17 & 22 CONDENSATE PUMP SERIES

Stainless Steel Mounting Tabs

Versatile multi-slot design Easily fits other major brands

3/8" Barb Check Valve •

Service w/o removing hose No tools needed

Larger 2.5 Qt. Tank ..

Pump runs less often Pump lasts longer



Rubber Feet on Tank •

Absorbs vibration Quieter operation

FEATURES & BENEFITS



Easily drain tank for servicing

New 3-Year Warranty

Proven reliability Backed with confidence



Bullseye Level on Lid

Confirm pump placement is level Quick and easy installation

6' Grounded Power Cord

Safe & easy power connection



OTHER CONDENSATE MANAGEMENT PRODUCTS

MS60 MINI SPLIT PUMPS

Condensate pumps for mini split systems up to 36,000 BTU



CEV500 EVAPORATOR

Condensate evaporator (500W) for commercial refrigeration



CT200 TREATMENT

Condensate treatment tablets to keep drain pans and lines clear



1502 SAFETY SWITCHES

Overflow safety switches for metal and plastic drain pans



G SERIES PUMPS

Bottom intake and submersible pumps for a range of applications

