



GP325 PARTS WASHER PUMP

FOR 115V,60Hz or 230V, 50/60Hz

Beckett's submersible pump line offers top of the line epoxy encapsulated (not oil filled), 115V,60Hz or 230V, 50/60Hz design to meet all your continuous duty requirements. They are low maintenance, environmentally safe, and can be used in a variety of industrial applications. Each pump features a heavy-duty motor for maximum output and reliability.

GP325VH is ideal for most solvent or aqueous parts washer solutions up to 340GPH@1ft. with a maximum pumping height of 12ft. This model has a FKM shaft seal and a threaded cord exit for mounting in a parts washer.

FEATURES:

for GP325VH

- Fully submersible
- Epoxy encapsulated
- FKM shaft seal
- Corrosion resistant polyester housing
- 1/4" MNPT discharge, fits 1/2" ID PVC tubing





| Model# | Н | W | L | Outlet | Inlet | Volts | Amps | Watts | Gallons per hour @ 60Hz / Rated Voltage | | | | | | Max | Temp | Weight | 6 Ft. Cord (No plug) | | (6 |
|---------|------|------|------|-----------|--------|-------|------|-------|---|-----|-----|-----|-----|-----|------------|------------|----------|-------------------------|----------|----|
| | | | | | | | | | 1′ | 2′ | 4′ | 6′ | 8′ | 10' | Lift (ft.) | Rising (F) | Lb. Each | (No plug) | C 744 US | |
| GP325VH | 4.3" | 2.8" | 5.2" | 1/4" MNPT | SCREEN | 115 | 0.8 | 50 | 340 | 330 | 300 | 260 | 205 | 135 | 12 | 110 | 4.0 | √ | √ | |
| GP325CH | 4.3" | 2.8" | 5.2" | 1/4" MNPT | SCREEN | 230 | 0.5 | 53 | 270 | 260 | 225 | 165 | 120 | - | 8.5 | 110 | 4.0 | √ | | √ |

DESIGNED FOR SUBMERSIBLE USE ONLY

Average Performance

