

CB to BK CROSS REFERENCE CHART

ALL CB15/20/22 MODELS HAVE BEEN REPLACED BY THE BK17/22

Discontinued CB Model	New BK Model*	Shutoff/ Max Lift (ft)	Input Volts	Tank Capacity	Max Temp	Outlet Check Valve
CB151UL	BK171UL	17'	115/120V	2.5 qt	150°F	3/8" O.D.
CB151LSUL	BK171LSUL	17'	115/120V	2.5 qt	150°F	3/8" O.D.
CB151TUL	BK171TUL	22'	115/120V	2.5 qt	150°F	3/8" O.D.
CB201UL	BK221UL	22'	115/120V	2.5 qt	150°F	3/8" O.D.
CB201LSUL	BK221LSUL	22'	115/120V	2.5 qt	150°F	3/8" O.D.
CB201TUL	BK221TUL	22'	115/120V	2.5 qt	150°F	3/8" O.D.
CB202UL	BK222UL	22'	230V	2.5 qt	150°F	3/8" O.D.
CB202TUL	BK222TUL	22'	230V	2.5 qt	150°F	3/8" O.D.
CB221UL	BK221UL	22'	115/120V	2.5 qt	150°F	3/8" O.D.

* UL - Standard unit 150°F max. water temp, T - Tubing included (20 ft of 3/8" I.D.), LS - Less safety switch

NEW BK17 & 22 CONDENSATE PUMP SERIES

FEATURES & BENEFITS

- Stainless Steel Mounting Tabs**
Versatile multi-slot design
Easily fits other major brands
- 3/8" Barb Check Valve**
Service w/o removing hose
No tools needed
- Larger 2.5 Qt. Tank**
Pump runs less often
Pump lasts longer
- Rubber Feet on Tank**
Absorbs vibration
Quieter operation
- Lift-to-Test Tab**
Quickly test/run pump
Easily drain tank for servicing
- New 3-Year Warranty**
Proven reliability
Backed with confidence
- Bullseye Level on Lid**
Confirm pump placement is level
Quick and easy installation
- 6' Grounded Power Cord**
Safe & easy power connection

3-YEAR WARRANTY

UL LISTED